

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43



Town of Southern Shores

5375 N. Virginia Dare Trail, Southern Shores, NC 27949

Phone 252-261-2394 / Fax 252-255-0876

info@southernshores-nc.gov

www.southernshores-nc.gov

TCA-2020-01

Ordinance 2020-XXXX

AN ORDINANCE AMENDING THE CODE OF ORDINANCES
OF THE TOWN OF SOUTHERN SHORES, NORTH CAROLINA

PART I. That Town Code Chapter 16 be replaced in its entirety as follows:

... Chapter 16 - FLOOD DAMAGE PREVENTION

Sec. 16-1. - Statutory authorization; findings of fact; purpose and objectives.

(a) *Statutory authorization.* **The Legislature of the State of North Carolina has in Part 6, Article 21 of Chapter 143; Article 6 of Chapter 153A; Article 8 of Chapter 160A; and Article 7, 9, and 11 of Chapter 160D (Effective January 1, 2021) of the North Carolina General Statutes, delegated to local governmental units the authority to adopt regulations designed to promote the public health, safety, and general welfare.**

Therefore, the Town Council of the Town of Southern Shores, North Carolina, does ordain as follows:

(b) *Findings of fact.*

(1) The floodprone areas within the jurisdiction of the Town of Southern Shores are subject to periodic inundation which results in loss of life, property, health and safety hazards, disruption of commerce and governmental services, extraordinary public expenditures of flood protection and relief, and impairment of the tax base, all of which adversely affect the public health, safety, and general welfare.

(2) These flood losses are caused by the cumulative effect of obstructions in floodplains causing increases in flood heights and velocities and by the occupancy in floodprone areas of uses vulnerable to floods or other hazards.

(c) *Statement of purpose.* It is the purpose of this chapter to promote public health, safety, and general welfare and to minimize public and private losses due to flood conditions within floodprone areas by provisions designed to:

(1) Restrict or prohibit uses that are dangerous to health, safety, and property due to water or erosion hazards or that result in damaging increases in erosion, flood heights or velocities;

(2) Require that uses vulnerable to floods, including facilities that serve such uses, be protected against flood damage at the time of initial construction;

(3) Control the alteration of natural floodplains, stream channels, and natural protective barriers, which are involved in the accommodation of floodwaters;

- 1 (4) Control filling, grading, dredging, and all other development that may increase erosion
2 or flood damage; and
- 3 (5) Prevent or regulate the construction of flood barriers that will unnaturally divert
4 floodwaters or which may increase flood hazards to other lands.
- 5 (d) *Objectives.* The objectives of this chapter are to:
- 6 (1) Protect human life, safety, and health;
- 7 (2) Minimize expenditure of public money for costly flood control projects;
- 8 (3) Minimize the need for rescue and relief efforts associated with flooding and generally
9 undertaken at the expense of the general public;
- 10 (4) Minimize prolonged business losses and interruptions;
- 11 (5) Minimize damage to public facilities and utilities (i.e., water and gas mains, electric,
12 telephone, cable and sewer lines, streets, and bridges) that are located in floodprone
13 areas;
- 14 (6) Help maintain a stable tax base by providing for the sound use and development of
15 floodprone areas; and
- 16 (7) Ensure that potential buyers are aware that property is in a special flood hazard area.
- 17 **(8) Minimize damage to private and public property due to flooding;**
- 18
- 19 **(9) Make flood insurance available to the community through the National Flood**
20 **Insurance Program;**
- 21
- 22 **(10) Maintain the natural and beneficial functions of floodplains;**
- 23
- 24 **(11) Mitigate flood risks in all areas of unincorporated Dare County the Town of**
25 **Southern Shores and its areas of extra territorial jurisdiction by implementing**
26 **local elevation standards for all Special Flood Hazards Areas and Shaded X and X**
27 **Zones.**

28

29 Sec. 16-2. - Definitions.

30 Unless specifically defined below, words or phrases used in this ordinance shall be interpreted so
31 as to give them the meaning they have in common usage and to give this ordinance it's most
32 reasonable application.

33

34 *Accessory structure (appurtenant structure)* means a structure located on the same parcel of
35 property as the principal structure and the use of which is incidental to the use of the principal
36 structure. Garages, carports and storage sheds are common urban accessory structures. Pole
37 barns, hay sheds and the like qualify as accessory structures on farms, and may or may not be
38 located on the same parcel as the farm dwelling or shop building. **For floodplain management**
39 **purposes, accessory structures are considered structures used for parking and storage**
40 **only. The definition used for floodplain management purposes may vary from similar**
41 **definitions found in the Southern Shores Zoning Ordinance.**

42 *Addition (to an existing building)* means an extension or increase in the floor area or height
43 of a building or structure.

44 **Alteration of a watercourse means a dam, impoundment, channel relocation, change**
45 **in channel alignment, channelization, or change in cross-sectional area of the channel or**

1 **the channel capacity, or any other form of modification which may alter, impede, retard or**
2 **change the direction and/or velocity of the riverine flow of water during conditions of the**
3 **base flood.**

4 *Appeal* means a request for a review of the Floodplain Administrator's interpretation of any
5 provision of this chapter.

6 ***Area of Shallow Flooding* means a designated Zone AO or AH on a community's Flood**
7 **Insurance Rate Map (FIRM) with base flood depths determined to be from one (1) to three**
8 **(3) feet. These areas are located where a clearly defined channel does not exist, where the**
9 **path of flooding is unpredictable and indeterminate, and where velocity flow may be**
10 **evident.**

11 *Area of special flood hazard. See Special flood hazard area (SFHA).*

12 *Base flood* means the flood having a one percent chance of being equaled or exceeded in
13 any given year.

14 *Base flood elevation (BFE)* means a determination of the water surface elevations of the
15 base flood as published in the Flood Insurance Study. When the BFE has not been provided in a
16 special flood hazard area, it may be obtained from engineering studies available from a federal,
17 state or other source, using FEMA approved engineering methodologies. This elevation, when
18 combined with the freeboard, establishes the regulatory flood protection elevation.

19 *Basement* means any area of the building having its floor subgrade (below ground level) on
20 all sides.

21 *Breakaway wall* means a wall that is not part of the structural support of the building and is
22 intended through its design and construction to collapse under specific lateral loading forces
23 without causing damage to the elevated portion of the building or the supporting foundation
24 system.

25 *Building. See Structure.*

26 *Chemical storage facility* means a building, portion of a building, or exterior area adjacent to
27 a building used for the storage of any chemical or chemically reactive products.

28 ***Coastal Area Management Act (CAMA)* means North Carolina's Coastal Area**
29 **Management Act. This act, along with the Dredge and Fill Law and the Federal Coastal**
30 **Zone Management Act, is managed through North Carolina Department of Environmental**
31 **Quality (NCDEQ) Division of Coastal Management (DCM).**

32 ***Coastal A Zone (CAZ)* means an area within a special flood hazard area, landward of a**
33 **V zone or landward of an open coast without mapped V zones; in a Coastal A Zone, the**
34 **principal source of flooding must be astronomical tides, storm surges, seiches, or**
35 **tsunamis, not riverine flooding. During the base flood conditions, the potential for wave**
36 **heights shall be greater than or equal to 1.5 feet. Coastal A Zones are not normally**
37 **designated on FIRMs. (see Limit of Moderate Wave Action (LiMWA)).**

38
39 *Coastal barrier resources system (CBRS)* consists of undeveloped portions of coastal and
40 adjoining areas established by the Coastal Barrier Resources Act (CoBRA) of 1982, the Coastal
41 Barrier Improvement Act (CBIA) of 1990, and subsequent revisions, and includes areas owned by
42 federal or state governments or private conservation organizations identified as otherwise
43 protected areas (OPA).

44 *Coastal high hazard area* means a special flood hazard area extending from offshore to the
45 inland limit of a primary frontal dune along an open coast and any other area subject to high
46 velocity wave action from storms or seismic sources. The area is designated on a flood insurance
47 rate map (FIRM), or other adopted flood map as determined in section 16-3(b), as zone VE.

1 **Design Flood** see “Regulatory Flood Protection Elevation.”

2
3 *Development* means any manmade change to improved or unimproved real estate,
4 including, but not limited to, buildings or other structures, mining, dredging, filling, grading, paving,
5 excavation or drilling operations, or storage of equipment or materials.

6 **Development Activity** means any activity defined as Development which will
7 necessitate a Floodplain Development Permit. This includes buildings, structures, and
8 non-structural items, including (but not limited to) fill, bulkheads, piers, pools, docks,
9 landings, ramps, and erosion control/stabilization measures.

10
11 **Digital Flood Insurance Rate Map (DFIRM)** means the digital official map of a
12 community, issued by the Federal Emergency Management Agency (FEMA), on which both
13 the Special Flood Hazard Areas and the risk premium zones applicable to the community
14 are delineated.

15
16 *Disposal* means, as defined in NCGS 130A-290(a)(6), the discharge, deposit, injection,
17 dumping, spilling, leaking, or placing of any solid waste into or on any land or water so that the
18 solid waste or any constituent part of the solid waste may enter the environment or be emitted
19 into the air or discharged into any waters, including groundwaters.

20 *Elevated building* means a non-basement building which has its lowest elevated floor raised
21 above ground level by foundation walls, shear walls, posts, piers, pilings, or columns.

22 **Enclosure/Enclosed Area** means that portion of an elevated building below the lowest
23 elevated floor that is either partially or fully shut in by rigid/solid walls and is located either
24 partially or fully below the RFPE.

25
26 *Encroachment* means the advance or infringement of uses, fill, excavation, buildings,
27 permanent structures or development into a special flood hazard area, which may impede or alter
28 the flow capacity of a floodplain.

29 *Existing building and existing structure* means any building and/or structure for which the
30 “start of construction” commenced before **January 1, 1975 November 27, 1979.**

31
32 *Existing manufactured home park or manufactured home subdivision* means a manufactured
33 home park or subdivision for which the construction of facilities for servicing the lots on which the
34 manufactured homes are to be affixed (including, at a minimum, the installation of utilities, the
35 construction of streets, and either final site grading or the pouring of concrete pads) was
36 completed before the initial effective date of the floodplain management regulations adopted
37 **November 27, 1979** by the community.

38 *Flood or flooding* means a general and temporary condition of partial or complete inundation
39 of normally dry land areas from:

- 40 (1) The overflow of inland or tidal waters; and/or
41 (2) The unusual and rapid accumulation or runoff of surface waters from any source.

42 *Flood insurance* means the insurance coverage provided under the National Flood
43 Insurance Program.

44 *Flood insurance rate map (FIRM)* means an official map of a community, issued by the
45 Federal Emergency Management Agency, on which both the special flood hazard areas and the
46 risk premium zones applicable to the community are delineated. (see also DFIRM)

47 *Flood Insurance Study (FIS)* means an examination, evaluation, and determination of flood
48 hazards, corresponding water surface elevations (if appropriate), flood hazard risk zones, and
49 other flood data in a community issued by the FEMA. The Flood Insurance Study report includes

1 Flood Insurance Rate Maps (FIRMs) and Flood Boundary and Floodway Maps (FBFMs), if
2 published.

3
4 *Flood Prone Area* see “Floodplain”

5
6 *Flood zone* means a geographical area shown on a Flood Hazard Boundary Map or Flood
7 Insurance Rate Map that reflects the severity or type of flooding in the area.

8 *Floodplain* means any land area susceptible to being inundated by water from any source.

9 *Floodplain administrator* means the individual appointed to administer and enforce the
10 floodplain management regulations.

11 *Floodplain development permit* means any type of permit that is required in conformance
12 with the provisions of this chapter, prior to the commencement of any development activity.

13 *Floodplain management* means the operation of an overall program of corrective and
14 preventive measures for reducing flood damage and preserving and enhancing, where possible,
15 natural resources in the floodplain, including, but not limited to, emergency preparedness plans,
16 flood control works, floodplain management regulations, and open space plans.

17 *Floodplain Management Regulations* means this ordinance and other zoning ordinances,
18 subdivision regulations, building codes, health regulations, special purpose ordinances, and other
19 applications of police power. This term describes federal, state or local regulations, in any
20 combination thereof, which provide standards for preventing and reducing flood loss and damage.

21 *Floodproofing* means any combination of structural and nonstructural additions, changes, or
22 adjustments to structures, which reduce or eliminate flood damage to real estate or improved real
23 property, water and sanitation facilities, structures, and their contents.

24 ***Flood-resistant material* means any building product [material, component or system]
25 capable of withstanding direct and prolonged contact (minimum 72 hours) with floodwaters
26 without sustaining damage that requires more than low-cost cosmetic repair. Any material
27 that is water-soluble or is not resistant to alkali or acid in water, including normal adhesives
28 for above-grade use, is not flood-resistant. Pressure-treated lumber or naturally decay-
29 resistant lumbers are acceptable flooring materials. Sheet-type flooring coverings that
30 restrict evaporation from below and materials that are impervious, but dimensionally
31 unstable are not acceptable. Materials that absorb or retain water excessively after
32 submergence are not flood-resistant. Please refer to Technical Bulletin 2, *Flood Damage-
33 Resistant Materials Requirements*, and available from the FEMA. Class 4 and 5 materials,
34 referenced therein, are acceptable flood-resistant materials.**

35
36 ***Floodway* means the channel of a river or other watercourse, including the area above
37 a bridge or culvert when applicable, and the adjacent land areas that must be reserved in
38 order to discharge the base flood without cumulatively increasing the water surface
39 elevation more than one (1) foot.**

40
41 *Freeboard* means the height added to the base flood elevation (BFE) to account for the
42 many unknown factors that could contribute to flood heights greater than the height calculated for
43 a selected size flood and floodway conditions, such as wave action, bridge openings, storm surge
44 or precipitation exceeding and the hydrological effect of urbanization on the watershed. The base
45 flood elevation plus the freeboard establishes the regulatory flood protection elevation.

46 *Functionally dependent facility* means a facility which cannot be used for its intended
47 purpose unless it is located in close proximity to water, such as a docking or port facility
48 necessary for the loading and unloading of cargo or passengers, shipbuilding, or ship repair. The
49 term does not include longterm storage, manufacture, sales, or service facilities.

1 *Hazardous waste management facility* means, as defined in NCGS 130A, Article 9, a facility
2 for the collection, storage, processing, treatment, recycling, recovery, or disposal of hazardous
3 waste.

4 *Highest adjacent grade (HAG)* means the highest natural elevation of the ground surface,
5 prior to construction, immediately next to the proposed walls of the structure.

6 *Historic structure* means any structure that is:

- 7 (1) Listed individually in the National Register of Historic Places (a listing maintained by the
8 U.S. Department of the Interior) or preliminarily determined by the Secretary of the Interior
9 as meeting the requirements for individual listing on the National Register;
- 10 (2) Certified or preliminarily determined by the Secretary of the Interior as contributing to the
11 historical significance of a registered historic district or a district preliminarily determined
12 by the Secretary to qualify as a registered historic district;
- 13 (3) Individually listed on a local inventory of historic landmarks in communities with a
14 Certified Local Government (CLG) Program; or
- 15 (4) Certified as contributing to the historical significance of a historic district designated by
16 a community with a Certified Local Government (CLG) Program. Certified Local
17 Government (CLG) Programs are approved by the U.S. Department of the Interior, in
18 cooperation with the state department of cultural resources through the state historic
19 preservation officer, as having met the requirements of the National Historic Preservation
20 Act of 1966, as amended in 1980.

21 ***Letter of Map Change (LOMC)* means an official determination issued by FEMA
22 that amends or revises an effective Flood Insurance Rate Map or Flood Insurance
23 Study. Letters of Map Change include:**

- 24 (a) ***Letter of Map Amendment (LOMA): An official amendment, by letter, to an
25 effective National Flood Insurance Program map. A LOMA is based on technical
26 data showing that a property had been inadvertently mapped as being in the
27 floodplain, but is actually on natural high ground above the base flood elevation.
28 A LOMA amends the current effective Flood Insurance Rate Map and establishes
29 that a specific property, portion of a property, or structure is not located in a
30 special flood hazard area.***
- 31 (b) ***Letter of Map Revision (LOMR): A revision based on technical data that may
32 show changes to flood zones, flood elevations, special flood hazard area
33 boundaries and floodway delineations, and other planimetric features.***
- 34 (c) ***Letter of Map Revision Based on Fill (LOMR-F): A determination that a structure
35 or parcel of land has been elevated by fill above the BFE and is, therefore, no
36 longer located within the special flood hazard area. In order to qualify for this
37 determination, the fill must have been permitted and placed in accordance with
38 the community's floodplain management regulations.***
- 39 (d) ***Conditional Letter of Map Revision (CLOMR): A formal review and comment as
40 to whether a proposed project complies with the minimum NFIP requirements
41 for such projects with respect to delineation of special flood hazard areas. A
42 CLOMR does not revise the effective Flood Insurance Rate Map or Flood
43 Insurance Study; upon submission and approval of certified as-built
44 documentation, a Letter of Map Revision may be issued by FEMA to revise the
45***

1 effective FIRM.

2
3 **Light Duty Truck** means any motor vehicle rated at 8,500 pounds Gross
4 **Vehicular Weight Rating** or less which has a vehicular curb weight of 6,000 pounds
5 **or less and which has a basic vehicle frontal area of 45 square feet or less as**
6 **defined in 40 CFR 86.082-2 and is:**

- 7
8 (a) **Designed primarily for purposes of transportation of property or is a derivation**
9 **of such a vehicle, or**
10 (b) **Designed primarily for transportation of persons and has a capacity of more than**
11 **12 persons; or**
12 (c) **Available with special features enabling off-street or off-highway operation and**
13 **use.**
14

15 **Limit of Moderate Wave Action (LiMWA)** means the boundary line given by FEMA on
16 **coastal map studies marking the extents of Coastal A Zones (CAZ).**

17 *Lowest adjacent grade (LAG)* means the elevation of the ground, sidewalk or patio slab
18 immediately next to the building, or deck support, after completion of the building.

19 **Local Elevation Standard** means a locally adopted elevation level used as the
20 **Regulatory Flood Protection Elevation (RFPE) in Shaded X and X zones or used in**
21 **conjunction with the BFE and freeboard standard to mitigate flood hazards in the AE, AO,**
22 **AH, VE zones, as depicted on the FIRMs for Southern Shores.**

23
24 *Lowest floor* means the lowest floor of the lowest enclosed area (including basement). An
25 unfinished or flood resistant enclosure, usable solely for parking of vehicles, building access, or
26 limited storage in an area other than a basement area is not considered a building's lowest floor,
27 provided that such an enclosure is not built so as to render the structure in violation of the
28 applicable non-elevation design requirements of this chapter.

29 *Manufactured home* means a structure, transportable in one or more sections, which is built
30 on a permanent chassis and designed to be used with or without a permanent foundation when
31 connected to the required utilities. The term "manufactured home" does not include a recreational
32 vehicle.

33 *Manufactured home park or subdivision* means a parcel (or contiguous parcels) of land
34 divided into two or more manufactured home lots for rent or sale.

35 **Map Repository.** means the location of the official flood hazard data to be applied for
36 **floodplain management. It is a central location in which flood data is stored and managed;**
37 **in North Carolina, FEMA has recognized that the application of digital flood hazard data**
38 **products carries the same authority as hard copy products. Therefore, the NCEM's**
39 **Floodplain Mapping Program websites house current and historical flood hazard data. For**
40 **effective flood hazard data, the NC FRIS website (<http://FRIS.NC.GOV/FRIS>) is the map**
41 **repository, and for historical flood hazard data the FloodNC website**
42 **(<http://FLOODNC.GOV/NCFLOOD>) is the map repository.**

43 *Market value* means the building value, not including the land value and that of any
44 accessory structures or other improvements on the lot. Market value may be established by

1 independent certified appraisal: replacement cost depreciated for age of building and quality of
2 construction (actual cash value): or adjusted tax assessed values.

3 *New construction* means structures for which the start of construction commenced **on or**
4 **after November 27, 1979, which is the effective date of the initial floodplain management**
5 **regulations** and includes any subsequent improvements to such structures.

6 *Otherwise Protected Area (OPA)* means an otherwise protected area.

7 *Post-FIRM* means construction or other development for which the start of construction
8 occurred on or after **November 27, 1979 May 13, 1972**, the effective date of the initial Flood
9 Insurance Rate Map.

10 *Pre-FIRM* means construction or other development for which the start of construction
11 occurred before **November 27, 1979 May 13, 1972**, the effective date of the initial Flood
12 Insurance Rate Map for the area.

13 ***Primary Frontal Dune (PFD)* means a continuous or nearly continuous mound or ridge**
14 **of sand with relatively steep seaward and landward slopes immediately landward and**
15 **adjacent to the beach and subject to erosion and overtopping from high tides and waves**
16 **during major coastal storms. The inland limit of the primary dune occurs at the point**
17 **where there is a distinct change from a relatively steep slope to a relatively mild slope.**
18 **This definition is used for floodplain management purposes and varies from the definition**
19 **used in the NC Division of Coastal Management regulations.**

20 *Principally above ground* means that at least 51 percent of the actual cash value of the
21 structure is above ground.

22 *Public safety and/or nuisance* means anything which is injurious to the safety or health of an
23 entire community or neighborhood, or any considerable number of persons, or unlawfully
24 obstructs the free passage or use, in the customary manner, of any navigable lake, river, bay,
25 stream, canal, or basin.

26 *Recreational vehicle (RV)* means a vehicle which is:

- 27 (1) Built on a single chassis;
28 (2) 400 square feet or less when measured at the largest horizontal projection;
29 (3) Designed to be self-propelled or permanently towable by a light-duty truck;
30 (4) Designed primarily not for use as a permanent dwelling, but as temporary living quarters
31 for recreational, camping, travel, or seasonal use, and
32 (5) Is fully licensed and ready for highway use.

33 ***Reference Level***

- 34 • **For structures within the Special Flood Hazard Areas designated as Zones AE**
35 **and AO the reference level is the bottom of the lowest floor or the bottom of the**
36 **lowest attendant utility including ductwork, whichever is lower, with only flood**
37 **resistant materials located below the reference level.**
- 38 • **For structures within the Special Flood Hazard Areas designated as Zone VE, the**
39 **reference level is the bottom of the lowest horizontal structural member of the**
40 **lowest floor or the bottom of the lowest attendant utility including ductwork,**
41 **whichever is lower.**

- 1 • For structures within Zones Shaded X or X, the reference level is the bottom of the
2 lowest floor or the bottom of the lowest attendant utility including ductwork
3 whichever is lower, with only flood resistant materials located below the reference
4 level.

5
6 *Regulatory Flood Protection Elevation (RFPE)* means in Special Flood Hazard Areas,
7 the “Base Flood Elevation” plus the “Freeboard” for those areas where base flood
8 elevations have been determined on the FIRM. It also means the base flood depth above
9 the highest adjacent grade or local elevation standards for those areas identified as AO
10 zones of the FIRM, or the local elevation standard for those areas identified as Shaded X
11 or X zones on the FIRM.

12
13 For Southern Shores the RFPE is as follows:

- 14
15 • In VE zones, the RFPE is the Base Flood Elevation as designated on the effective
16 FIRM plus 3 feet of freeboard OR an elevation to a minimum of 14 feet NAVD 1988.
- 17
18 • In AE zones, the RFPE is the Base Flood Elevation as designated on the effective
19 FIRM plus 3 feet of freeboard OR an elevation to or above 8 feet NAVD 1988,
20 whichever is greater.
- 21
22 • In AO zones, the RFPE is the designated base flood depth on the effective FIRM
23 above the highest natural adjacent grade ~~plus 3 feet of freeboard OR an elevation~~
24 to or above 8 feet NAVD 1988, whichever is greater.
- 25
26 • In Shaded X and X zones, the RFPE is 8 feet NAVD 1988 OR the natural grade
27 elevation if the natural grade is greater than 8 feet NAVD 1988.

28
29 *Remedy a violation* means to bring the structure or other development into compliance with
30 state and community floodplain management regulations or, if this is not possible, to reduce the
31 impacts of its noncompliance. Ways that impacts may be reduced include protecting the structure
32 or other affected development from flood damages, implementing the enforcement provisions of
33 the chapter or otherwise deterring future similar violations, or reducing federal financial exposure
34 with regard to the structure or other development.

35 *Riverine* means relating to, formed by, or resembling, a river (including tributaries), stream,
36 brook, etc.

37 *Salvage yard* means any nonresidential property used for the storage, collection, and/or
38 recycling of any type of equipment, and includes, but is not limited to, vehicles, appliances and
39 related machinery.

40 *Sand Dunes* means naturally occurring accumulations of sand in ridges or mounds landward
41 of the beach.

1 **Shaded X Zone means areas of moderate flood hazard shown on the FIRM and are the**
2 **areas between the limits of the base flood and the 0.2% annual chance for flood. Also**
3 **commonly referred to as the 500-year flood.**

4 *Shear Wall* means walls used for structural support but not structurally joined or enclosed at
5 the end (except by breakaway walls). Shear walls are parallel or nearly parallel to the flow of the
6 water.

7 *Solid waste disposal facility* means any facility involved in the disposal of solid waste, as
8 defined in NCGS 130A-290(a)

9 *Solid waste disposal site* means, as defined in NCGS 130A-290(a)(36), any place at which
10 solid wastes are disposed of by incineration, sanitary landfill, or any other method.

11 *Special Flood Hazard Area (SFHA)* means the land in the floodplain subject to a one percent
12 or greater chance of being flooded in any given year, as determined in Section 16-3(b) of this
13 chapter.

14 *Start of construction* includes substantial improvement, and means the date the building
15 permit was issued, provided the actual start of construction, repair, reconstruction, rehabilitation,
16 addition placement, or other improvement was within 180 days of the permit date. The actual start
17 means either the first placement of permanent construction of a structure on a site, such as the
18 pouring of slab or footings, the installation of piles, the construction of columns, or any work
19 beyond the stage of excavation; or the placement of a manufactured home on a foundation.
20 Permanent construction does not include land preparation, such as clearing, grading, and filling;
21 nor does it include the installation of streets and/or walkways; nor does it include excavation for a
22 basement, footings, piers, or foundations or the erection of temporary forms; nor does it include
23 the installation on the property of accessory buildings, such as garages or sheds not occupied as
24 dwelling units or not part of the main structure. For a substantial improvement, the actual start of
25 construction means the first alteration of any wall, ceiling, floor, or other structural part of the
26 building, whether or not that alteration affects the external dimensions of the building.

27 *Structure* means a walled and roofed building, a manufactured home, or a gas, liquid, or
28 liquefied gas storage tank that is principally above ground.

29 *Substantial damage* means damage of any origin sustained by a structure during any one-
30 year period whereby the cost of restoring the structure to its before-damaged condition would
31 equal or exceed 50 percent of the market value of the structure before the damage occurred. See
32 definition of *Substantial improvement*. The term "substantial damage" also means flood-related
33 damage sustained by a structure on two separate occasions during a ten-year period for which
34 the cost of repairs at the time of each such flood event, on the average, equals or exceeds 25
35 percent of the market value of the structure before the damage occurred.

36 *Substantial improvement* means any combination of repairs, reconstruction, rehabilitation,
37 addition, or other improvement of a structure, taking place during any one-year period for which
38 the cost equals or exceeds 50 percent of the market value of the structure before the start of
39 construction of the improvement. The one-year period shall be based on the date a Certificate of
40 Occupancy is issued for the improvement. This term includes structures which have incurred
41 substantial damage, regardless of the actual repair work performed. The term does not, however,
42 include either:

- 43 (1) Any correction of existing violations of state or community health, sanitary, or safety code
44 specifications which have been identified by the community code enforcement official and
45 which are the minimum necessary to ensure safe living conditions; or
- 46 (2) Any alteration of a historic structure, provided that the alteration will not preclude the
47 structure's continued designation as a historic structure and the alteration is approved by
48 variance issued pursuant to Section 16-4 (e).

1 **Technical Bulletin and Technical Fact Sheet** means a FEMA publication that provides
2 guidance concerning the building performance standards of the NFIP, which are contained
3 in Title 44 of the U.S. Code of Federal Regulations at Section 60.3. The bulletins and fact
4 sheets are intended for use primarily by State and local officials responsible for
5 interpreting and enforcing NFIP regulations and by members of the development
6 community, such as design professionals and builders. New bulletins, as well as updates
7 of existing bulletins, are issued periodically as needed. The bulletins do not create
8 regulations; rather they provide specific guidance for complying with the minimum
9 requirements of existing NFIP regulations.

10
11 **Temperature Controlled** means having the temperature regulated by a heating and/or
12 cooling system, built-in or appliance.

13
14 *Variance* means a grant of relief from the requirements of this chapter.

15 *Violation* means the failure of a structure or other development to be fully compliant with the
16 community's floodplain management regulations. A structure or other development without the
17 elevation certificate, other certifications, or other evidence of compliance required in sections 16-4
18 and 16-5 is presumed to be in violation until such time as that documentation is provided.

19 **Water surface elevation (WSE)** means the height, in relation to NAVD 1988, of floods
20 of various magnitudes and frequencies in the floodplains of coastal or riverine areas.

21 *Watercourse* means a lake, river, creek, stream, wash, channel or other topographic feature
22 on or over which waters flow at least periodically. The term "watercourse" includes specifically
23 designated areas in which substantial flood damage may occur.

24 **X Zone** means the areas of minimal flood hazard shown on the FIRM which are areas
25 outside of the Special Flood Hazards Areas and higher than the elevation of the 0.2%
26 annual flood chance. Also referred to as Unshaded X Zone.

27
28 Sec. 16-3. - General provisions.

29 (a) *Lands to which this chapter applies.* This chapter shall apply to all areas within the jurisdiction,
30 including extraterritorial jurisdictions (ETJs), if applicable, of the **Town of Southern Shores**.

31 (b) *Basis for establishing the special flood hazard areas.* The Special Flood Hazard Areas are
32 those identified under the Cooperating Technical State (CTS) agreement between the State of
33 North Carolina and FEMA in its FIS dated **June 19, 2020** for **Dare County** and associated
34 DFIRM panels, including any digital data developed as part of the FIS, which are adopted by
35 reference and declared a part of this ordinance **and all revisions thereto after January 1, 2021**.
36 Future revisions to the FIS and DFIRM panels that do not change flood hazard data within the
37 jurisdictional authority of **Southern Shores** are also adopted by reference and declared a part of
38 this ordinance. Subsequent Letter of Map Revisions (LOMRs) and/or Physical Map Revisions
39 (PMRs) shall be adopted within 3 months.

40
41 **(c) Establishment of Floodplain Development Permit.**

42 **A Floodplain Development Permit shall be required in conformance with the provisions of this**
43 **ordinance prior to the commencement of any development activities within Special Flood Hazard**
44 **Areas and Shaded X and X Zones, determined in accordance with the provisions of Section 16-3**
45 **(b) of this ordinance.**

1 **(e)(d) Establishment of Local Elevation Standard to serve as Regulatory Flood Protection**
2 **Elevation in Shaded X and Unshaded X zones**

3 A locally adopted elevation standard shall apply to any Shaded X or X zone as identified
4 on the effective DFIRMs for Southern Shores or used in conjunction with the BFE and
5 freeboard standard to mitigate flood hazards in the AE, AO, AH, VE zones, as depicted on
6 the FIRMs for Southern Shores. These areas may be vulnerable to flooding from storm
7 surge, wind-driven tides, and excessive rainfall associated with storm systems. Many of
8 these areas have flooded during past storm events and continue to remain at risk to
9 flooding. Therefore, a local elevation standard and other floodplain development
10 standards including Regulatory Flood Protection Elevation have been determined by the
11 Town of Southern Shores to be appropriate for these Shaded X and X zones as defined in
12 **Section 16-2**. All development activities in any Shaded X or X zone shall conform to the
13 provisions set forth in this Chapter.
14

15 **(e)(e) Compliance.** No structure or land shall hereafter be located, extended, converted, altered,
16 or developed in any way without full compliance with the terms of this chapter and other
17 applicable regulations.

18 **(e)(f) Abrogation and greater restrictions.** This chapter is not intended to repeal, abrogate, or
19 impair any existing easements, covenants, or deed restrictions. However, where this chapter
20 and another conflict or overlap, whichever imposes the more stringent restrictions shall prevail.

21 **(f)(g) Interpretation.** In the interpretation and application of this chapter, all provisions shall be:

- 22 (1) Considered as minimum requirements;
- 23 (2) Liberally construed in favor of the Town Council; and
- 24 (3) Deemed neither to limit nor repeal any other powers granted under state statutes.

25 **(g)(h) Warning and disclaimer of liability.** The degree of flood protection required by this
26 chapter is considered reasonable for regulatory purposes and is based on scientific
27 and engineering consideration. Larger floods can and will occur. Actual flood heights
28 may be increased by manmade or natural causes. This chapter does not imply that land
29 outside the special flood hazard areas or uses permitted within such areas will be free
30 from flooding or flood damages. This chapter shall not create liability on the part of the
31 Town or by any officer or employee thereof for any flood damages that result from
32 reliance on this chapter or any administrative decision lawfully made hereunder.

33 **(h)(i) Penalties for Violations.** Violation of the provisions of this ordinance or failure to
34 comply with any of its requirements, including violation of conditions and safeguards
35 established in connection with grants of variance or special exceptions, shall constitute a
36 Class 1 misdemeanor pursuant to NC G.S. § 143-215.58. Any person who violates this
37 ordinance or fails to comply with any of its requirements shall, upon conviction thereof, be
38 fined not more than \$100.00 or imprisoned for not more than thirty (30) days, or both.
39 Each day such violation continues shall be considered a separate offense. Nothing herein
40 contained shall prevent Southern Shores from taking such other lawful action as is
41 necessary to prevent or remedy any violation.
42

43 Sec. 16-4. - Administration.

44 (a) **Designation of floodplain administrator.** The Town Manager or his or her designee, hereinafter
45 referred to as the Floodplain Administrator, is hereby appointed to administer and implement
46 the provisions of this section. **In instances where the Floodplain Administrator receives**
47 **assistance from others to complete tasks to administer and implement this ordinance,**
48 **the Floodplain Administrator shall be responsible for the coordination and**

1 **community's overall compliance with the National Flood Insurance Program and the**
2 **provisions of this ordinance.**

3 (b) *Floodplain development application, permit and certification requirements.*

4 (1) *Application requirements.* An application for a floodplain development permit shall be
5 made to the Floodplain Administrator prior to any development activities located within
6 special flood hazard areas. The following items shall be presented to the floodplain
7 administrator to apply for a floodplain development permit:

8 a. A plot plan drawn to scale which shall include, but shall not be limited to, the following
9 specific details of the proposed floodplain development:

- 10 1. The nature, location, dimensions, and elevations of the area of
11 development/disturbance and existing and proposed structures, utility systems,
12 grading/pavement areas, fill materials, storage areas, drainage facilities, and
13 other development;
- 14 2. The boundary of **any** Special Flood Hazard Area **or any Shaded X or X Zone**
15 as delineated on the FIRM or other flood map, as determined in section 16-
16 3(b), or a statement that the entire lot is within the Special Flood Hazard Area;
- 17 3. Flood zone(s), **including any Shaded X or X Zone**, designation of the
18 proposed development area, as determined on the FIRM or other flood map,
19 as determined in section 16-3(b);
- 20 4. The boundary of the floodway or non-encroachment area as determined in
21 section 16-3(b);
- 22 5. The base flood elevation (BFE) **and/or Regulatory Flood Protection**
23 **Elevation**, where provided as set forth in *Section 16-3(b); Section 16-4(c)(11)*
24 *and (12); or Section 16-5(b)*;
- 25 6. The old and new location of any watercourse that will be altered or relocated
26 as a result of proposed development;
- 27 7. The boundary and designation date of the Coastal Barrier Resource System
28 (CBRS) area or otherwise protected areas (OPA), if applicable; and
- 29 8. Certification of the plot plan by a registered land surveyor or professional
30 engineer.

31 b. Proposed elevation, and method thereof, of all development including, but not limited
32 to:

- 33 1. Elevation in relation to **NAVD 1988**, of the proposed reference level (including
34 basement) of all structures;
- 35 2. Elevation in relation to **NAVD 1988** to which any non-residential structure in
36 zones A, AE, AH, AO, A99, **Shaded X or X Zone** will be floodproofed; and
- 37 3. Elevation in relation to **NAVD 1988** to which any proposed utility systems will
38 be elevated or floodproofed;

39 c. If floodproofing, a floodproofing certificate (FEMA Form 086-0-34) with supporting
40 data and an operational plan that includes, but is not limited to, installation, exercise,
41 and maintenance of floodproofing measures.

42 d. A foundation plan, drawn to scale, which shall include details of the proposed
43 foundation system to ensure all provisions of this chapter are met. These details
44 include but are not limited to:

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47

1. The proposed method of elevation, if applicable (i.e., fill, solid foundation perimeter wall, solid backfilled foundation, open foundation on columns/posts/piers/piles/shear walls) and
 2. Openings to facilitate equalization of hydrostatic flood forces on walls in accordance with *Section 16-5(b)(4)*, when solid foundation perimeter walls are used in zones A, AE, AH, AO, A99, **Shaded X or X Zone**.
 3. The following, in Coastal High Hazard Areas, in accordance with *Section 16-5(b)(4)d and Section 16-5(f)*:
 - (i) **V-Zone Certification with accompanying plans and specifications verifying the engineered structure and any breakaway wall designs; in addition, prior to the Certificate of Compliance/Occupancy issuance, a registered professional engineer or architect shall certify the finished construction is compliant with the design, specifications and plans for VE Zone construction.**
 - (ii) Plans for open wood latticework or insect screening, if applicable;
 - (iii) Plans for nonstructural fill, if applicable. If nonstructural fill is proposed, it must be demonstrated through coastal engineering analysis that the proposed fill would not result in any increase in the base flood elevation or otherwise cause adverse impacts by wave ramping and deflection onto the subject structure or adjacent properties.
 - e. Usage details of any enclosed areas below the regulatory flood protection elevation.
 - f. Plans and/or details for the protection of public utilities and facilities such as sewer, gas, electrical, and water systems to be located and constructed to minimize flood damage.
 - g. Copies of all other local, state and federal permits required prior to floodplain development permit issuance (wetlands, endangered species, erosion and sedimentation control, CAMA, riparian buffers, mining, etc.).
 - h. Documentation for placement of recreational vehicles and/or temporary structures, when applicable, to ensure section 16-5(b)(6) and (7) of this chapter are met.
 - i. A description of proposed watercourse alteration or relocation, when applicable, including an engineering report on the effects of the proposed project on the flood-carrying capacity of the watercourse and the effects to properties located both upstream and downstream; and a map (if not shown on plot plan) showing the location of the proposed watercourse alteration or relocation.
 - j. In Shaded X and X zones, a survey prepared by a licensed North Carolina surveyor may be used to demonstrate the natural grades of the parcel relative to the RFPE of 8 feet.**
- (2) *Permit requirements.* The floodplain development permit shall include, but not be limited to:
- a. **A complete description of all the development to be permitted under the floodplain development permit (e.g. house, garage, pool, septic, bulkhead, cabana, pier, bridge, mining, dredging, filling, grading, paving, excavation or drilling operations, or storage of equipment or materials, etc.).**
 - b. The **flood zone** determination for the proposed development per available data specified in *Section 16-3(b)* **and** (c) **and** (d).

- 1 c. The regulatory flood protection elevation required for the reference level and all
2 attendant utilities.
- 3 d. The regulatory flood protection elevation required for the protection of all public
4 utilities.
- 5 e. All certification submittal requirements with timelines.
- 6 f. **A statement that no fill material or other development shall encroach into the
7 floodway or non-encroachment area of any watercourse, as applicable.**
- 8 g. The flood openings requirements, if in zones A, AE, AH, AO, A99, **Shaded X or X
9 Zone.**
- 10 h. **Limitation of below RFPE enclosure uses – parking, building access and
11 limited storage only.**
- 12 i. **A statement, if in Zone VE, that there shall be no alteration of sand dunes
13 which would increase potential flood damage.**
- 14 j. **A statement, if in zone VE, that there shall be no fill used for structural support.**
- 15 k. **A statement, that all material below RFPE must be flood resistant materials.**

16 (3) *Certification requirements.*

- 17 a. *Elevation certificates for AE, AO, VE, Shaded X and X Zones.*
 - 18 1. **An under construction elevation certificate is required prior to completion
19 of the framing/sheathing inspection by the Town. It shall be the duty of
20 the permit holder to submit to the Floodplain Administrator a certification
21 of the elevation of the reference level in relation to mean sea level. The
22 Floodplain Administrator shall review the certificate data submitted.
23 Deficiencies detected by such review shall be corrected by the permit
24 holder immediately and prior to further work being permitted to proceed.
25 Failure to submit the certification or failure to make required corrections
26 shall be cause to issue a stop work order for the project.**
 - 27 2. **A final Finished Construction Elevation Certificate (FEMA Form 086-0-
28 33) is required after construction is completed and prior to Certificate of
29 Compliance/Occupancy issuance. It shall be the duty of the permit
30 holder to submit to the Floodplain Administrator a certification of final
31 as-built construction of the elevation of the reference level and all
32 attendant utilities. The Floodplain Administrator shall review the
33 certificate data submitted. Deficiencies detected by such review shall
34 be corrected by the permit holder immediately and prior to Certificate of
35 Compliance/Occupancy issuance. In some instances, another
36 certification may be required to certify corrected as-built construction.
37 Failure to submit the certification or failure to make required corrections
38 shall be cause to withhold the issuance of a Certificate of
39 Compliance/Occupancy. The Finished Construction Elevation
40 Certificate certifier shall provide at least 2 photographs showing the
41 front and rear of the building taken within 90 days from the date of
42 certification. The photographs must be taken with views confirming the
43 building description and diagram number provided in Section A. To the
44 extent possible, these photographs should show the entire building
45 including foundation. If the building has split-level or multi-level areas,
46 provide at least 2 additional photographs showing side views of the
47 building. In addition, when applicable, provide a photograph of the
48 foundation showing a representative example of the flood openings or**

1 vents. All photographs must be in color and measure at least 3" x 3".
2 Digital photographs are acceptable.

3 3. In Shaded X and X zones, the submission of the under construction
4 elevation certificate and the finished construction elevation certificate
5 may be waived if a survey of the parcel was used to certify the natural
6 grade of the parcel was to or above 8 feet NAVD 1988 at the time of
7 permit application. In lieu of the finished construction elevation
8 certificate, an as-built survey of the parcel shall be submitted to certify
9 the finished grade of the parcel is compliant with the RFPE or 8 feet
10 NAVD 1988 or above.

11
12 b. *Floodproofing certificate.*

13 (1) If non-residential floodproofing is used to meet the Regulatory Flood
14 Protection Elevation requirements, a Floodproofing Certificate (FEMA Form
15 086-0-34), with supporting data, an operational plan, and an inspection and
16 maintenance plan are required prior to the actual start of any new
17 construction. It shall be the duty of the permit holder to submit to the
18 Floodplain Administrator a certification of the floodproofed design elevation
19 of the reference level and all attendant utilities, in relation to NAVD 1988.
20 Floodproofing certification shall be prepared by or under the direct
21 supervision of a professional engineer or architect and certified by same.
22 The Floodplain Administrator shall review the certificate data, the
23 operational plan, and the inspection and maintenance plan. Deficiencies
24 detected by such review shall be corrected by the applicant prior to permit
25 approval. Failure to submit the certification or failure to make required
26 corrections shall be cause to deny a Floodplain Development Permit. Failure
27 to construct in accordance with the certified design shall be cause to
28 withhold the issuance of a Certificate of Compliance/Occupancy.

29 (2) A final Finished Construction Floodproofing Certificate (FEMA Form 086-0-
30 34), with supporting data, an operational plan, and an inspection and
31 maintenance plan are required prior to the issuance of a Certificate of
32 Compliance/Occupancy. It shall be the duty of the permit holder to submit to
33 the Floodplain Administrator a certification of the floodproofed design
34 elevation of the reference level and all attendant utilities, in relation to NAVD
35 1988. Floodproofing certificate shall be prepared by or under the direct
36 supervision of a professional engineer or architect and certified by same.
37 The Floodplain Administrator shall review the certificate data, the
38 operational plan, and the inspection and maintenance plan. Deficiencies
39 detected by such review shall be corrected by the applicant prior to
40 Certificate of Occupancy. Failure to submit the certification or failure to
41 make required corrections shall be cause to deny a Floodplain Development
42 Permit. Failure to construct in accordance with the certified design shall be
43 cause to deny a Certificate of Compliance/Occupancy.

44
45 c. *Engineered foundation certification.* If a manufactured home is placed within zone A,
46 AE, AH, AO, Shaded X and X zone and the elevation of the chassis is more than
47 36 inches in height above grade, an engineered foundation certification is required
48 per Section 16-5(b)(3)(b).

49 d. *Watercourse alteration or relocation.* If a watercourse is to be altered or relocated, a
50 description of the extent of watercourse alteration or relocation; a professional
51 engineer's certified report on the effects of the proposed project on the flood-carrying

1 capacity of the watercourse and the effects to properties located both upstream and
2 downstream; and a map showing the location of the proposed watercourse alteration
3 or relocation shall all be submitted by the permit applicant prior to issuance of a
4 floodplain development permit.

5 e. *Certification exemptions.* The following structures, if located within zone A, AE, AH,
6 AO, **Shaded X and X zone**, are exempt from the elevation/floodproofing
7 certification requirements specified in *Section 16-5 (b)(3)a and b*.

- 8 1. Recreational vehicles meeting requirements of *Section 16-5(b)(6)(a)*;
- 9 2. Temporary structures meeting requirements of *Section 16-5(b)(7)*; and
- 10 3. Accessory structures **150 square feet or less and** meeting requirements of
11 *Section 16-5(b)(8)*.

12 f. **V-zone certification. A V-zone certification with accompanying design plans**
13 **and specifications is required prior to the issuance of a floodplain**
14 **development permit within coastal high hazard areas. It shall be the duty of**
15 **the permit applicant to submit to the floodplain administrator said certification**
16 **to ensure the design standards of this section are met. A registered**
17 **professional engineer or architect shall develop or review the structural**
18 **design, plans, and specifications for construction and certify that the design**
19 **and methods of construction to be used are in accordance with accepted**
20 **standards of practice for meeting the provisions of this chapter. This**
21 **certification is not a substitute for an elevation certificate. In addition, prior to**
22 **the Certificate of Compliance/Occupancy issuance, a registered professional**
23 **engineer or architect shall certify the finished construction is compliant with**
24 **the design, specifications and plans for VE Zone construction.**

25 **(4) Determinations for existing buildings and structures.**
26

27 **For applications for building permits to improve buildings and structures, including**
28 **alterations, movement, relocation, enlargement, replacement, repair, change of**
29 **occupancy, additions, rehabilitations, renovations, substantial improvements,**
30 **repairs of substantial damage, and any other improvement of or work on such**
31 **buildings and structures, the Floodplain Administrator, in coordination with the**
32 **Building Inspector, shall:**

- 34 (a) **Estimate the market value, or require the applicant to obtain an appraisal of the**
35 **market value prepared by a qualified independent appraiser, of the building or**
36 **structure before the start of construction of the proposed work; in the case of**
37 **repair, the market value of the building or structure shall be the market value**
38 **before the damage occurred and before any repairs are made;**
- 39 (b) **Compare the cost to perform the improvement, the cost to repair a damaged**
40 **building to its pre-damaged condition, or the combined costs of improvements**
41 **and repairs, if applicable, to the market value of the building or structure;**
- 42 (c) **Determine and document whether the proposed work constitutes substantial**
43 **improvement or repair of substantial damage; and**
- 44 (d) **Notify the applicant if it is determined that the work constitutes substantial**
45 **improvement or repair of substantial damage and that compliance with the**
46 **flood resistant construction requirements of the NC Building Code and this**
47 **ordinance is required.**
48
49
50
51

- 1 (c) *Duties and responsibilities of the Floodplain Administrator.* The floodplain administrator shall
2 perform, but not be limited to, the following duties:
- 3 (1) Review all floodplain development applications and issue permits for all proposed
4 development within special flood hazard areas to ensure that the requirements of this
5 chapter have been satisfied.
- 6 (2) Review all proposed development to assure that all necessary local, state and federal
7 permits have been received, including Section 404 of the Federal Water Pollution Control
8 Act Amendments of 1972, 33 U.S.C. 1334.
- 9 (3) Notify adjacent communities and the North Carolina Department of Public Safety, Division
10 of Emergency Management, State Coordinator for the National Flood Insurance Program
11 prior to any alteration or relocation of a watercourse, and submit evidence of such
12 notification to the Federal Emergency Management Agency (FEMA).
- 13 (4) Assure that maintenance is provided within the altered or relocated portion of said
14 watercourse so that the flood-carrying capacity is maintained.
- 15 (5) Prevent encroachments into floodways and non-encroachment areas unless the
16 certification and flood hazard reduction provisions of Section 16-5 are met.
- 17 (6) Obtain actual elevation (in relation to NAVD 1988) of the reference level (including
18 basement) and all attendant utilities of all new or substantially improved structures, in
19 accordance with Section 16-4 (b)(3) of this section.
- 20 (7) Obtain actual elevation (in relation to NAVD 1988) to which all new and substantially
21 improved structures and utilities have been floodproofed, in accordance with Section 16-
22 4 (b)(3) of this section.
- 23 (8) Obtain actual elevation (in relation to NAVD 1988) of all public utilities in accordance with
24 Section 16-4 (b)(3) of this section.
- 25 (9) When floodproofing is utilized for a particular structure, obtain certifications from a
26 registered professional engineer or architect in accordance with Section 16-4 (b)(3) of
27 this section and Section 16-5(b)(2).
- 28 (10) Where interpretation is needed as to the exact location of boundaries of the Special Flood
29 Hazard Areas, **Shaded X or X Zones**, floodways, or non-encroachment areas (for
30 example, where there appears to be a conflict between a mapped boundary and actual
31 field conditions), make the necessary interpretation. The person contesting the location
32 of the boundary shall be given a reasonable opportunity to appeal the interpretation as
33 provided in this chapter.
- 34 (11) When base flood elevation (BFE) data has not been provided in accordance with Section
35 16-3(b), obtain, review, and reasonably utilize any base flood elevation (BFE) data, along
36 with floodway data or non-encroachment area data, available from a federal, state, or
37 other source, including data developed pursuant to Section 16-5, in order to administer
38 the provisions of this chapter.
- 39 (12) When base flood elevation (BFE) data is provided but no floodway nor non-encroachment
40 area data has been provided in accordance with section 16-3(b), obtain, review, and
41 reasonably utilize any floodway data or non-encroachment area data available from a
42 federal, state, or other source in order to administer the provisions of this chapter.
- 43 (13) Permanently maintain all records that pertain to the administration of this chapter and
44 make these records available for public inspection.
- 45 (14) Make on-site inspections of work in progress. As the work pursuant to a floodplain
46 development permit progresses, the floodplain administrator shall make as many
47 inspections of the work as may be necessary to ensure that the work is being done
48 according to the provisions of this chapter and the terms of the permit. In exercising this

1 power, the floodplain administrator has a right, upon presentation of proper credentials,
2 to enter on any premises within the jurisdiction of the town at any reasonable hour for the
3 purposes of inspection or other enforcement action.

4 (15) Issue stop work orders as required. Whenever a building or part thereof is being
5 constructed, reconstructed, altered, or repaired in violation of this section, the floodplain
6 administrator may order the work to be immediately stopped. The stop work order shall
7 be in writing and directed to the person doing the work. The stop work order shall state
8 the specific work to be stopped, the specific reason(s) for the stoppage, and the
9 condition(s) under which the work may be resumed. Violation of a stop work order
10 constitutes a misdemeanor.

11 (16) Revoke floodplain development permits as required. The floodplain administrator may
12 revoke and require the return of the floodplain development permit by notifying the permit
13 holder in writing stating the reason(s) for the revocation. Permits shall be revoked for any
14 substantial departure from the approved application, plans, or specifications; for refusal
15 or failure to comply with the requirements of state or local laws; or for false statements or
16 misrepresentations made in securing the permit. Any floodplain development permit
17 mistakenly issued in violation of an applicable state or local law may also be revoked.

18 (17) Make periodic inspections throughout all special flood hazard areas within the jurisdiction
19 of the community. The floodplain administrator and each member of his or her inspections
20 department shall have a right, upon presentation of proper credentials, to enter on any
21 premises within the territorial jurisdiction of the department at any reasonable hour for the
22 purposes of inspection or other enforcement action.

23 (18) Follow through with corrective procedures of *Section 16-4(d)* of this section.

24 (19) Review, provide input, and make recommendations for variance requests.

25 **(20) Maintain a current map repository to include, but not be limited to, historical and**
26 **effective FIS report, historical and effective FIRM and other official flood maps and**
27 **studies adopted in accordance with *Section 16-3(b)*, including any revisions**
28 **thereto, including Letters of Map Change, issued by FEMA. Notify state and FEMA**
29 **of mapping needs.**

30 (21) Coordinate revisions to FIS reports and FIRMs, including letters of map revision based
31 on fill (LOMR-F's) and Letters of Map Revision (LOMR's).

32 (d) *Corrective procedures.*

33 (1) *Violations to be corrected.* When the Floodplain Administrator finds violations of
34 applicable state and local laws, it shall be his or her duty to notify the owner or occupant
35 of the building of the violation. The owner or occupant shall immediately remedy each of
36 the violations of law cited in such notification.

37 (2) *Actions in event of failure to take corrective action.* If the owner of a building or property
38 shall fail to take prompt corrective action, the floodplain administrator shall give the owner
39 written notice, by certified or registered mail to the owner's last known address or by
40 personal service, stating:

- 41 a. That the building or property is in violation of the floodplain management regulations;
- 42 b. That a hearing will be held before the Floodplain Administrator at a designated place
43 and time, not later than ten (10) days after the date of the notice, at which time the
44 owner shall be entitled to be heard in person or by counsel and to present arguments
45 and evidence pertaining to the matter; and
- 46 c. That following the hearing, the Floodplain Administrator may issue an order to alter,
47 vacate, or demolish the building; or to remove fill as appears appropriate.

1 (3) *Order to take corrective action.* If, upon a hearing held pursuant to the notice prescribed
2 above, the floodplain administrator shall find that the building or development is in
3 violation of this chapter, they shall issue an order in writing to the owner, requiring the
4 owner to remedy the violation within a specified time period, not less than sixty (60)
5 calendar days, **nor more than 180 calendar days**. Where the Floodplain Administrator
6 finds that there is imminent danger to life or other property, they may order that corrective
7 action be taken in such lesser period as may be feasible.

8 (4) *Appeal.* Any owner who has received an order to take corrective action may appeal the
9 order to the local elected town council by giving notice of appeal in writing to the
10 Floodplain Administrator and the clerk within ten (10) days following issuance of the final
11 order. In the absence of an appeal, the order of the Floodplain Administrator shall be
12 final. The local Town Council shall hear an appeal within a reasonable time and may
13 affirm, modify and affirm, or revoke the order.

14 (5) ***Failure to comply with order.* If the owner of a building or property fails to comply
15 with an order to take corrective action for which no appeal has been made or fails
16 to comply with an order of the Town Council following an appeal, the owner shall
17 be guilty of a Class 1 misdemeanor pursuant to NC G.S. § 143-215.58 and shall be
18 punished at the discretion of the court.**

19 (e) *Variance procedures.*

20 **These procedures apply in AE zones, AO zones, VE zones, Shaded X zones and X zones**
21 **as depicted on the FIRMs for Southern Shores.**

22 (1) The **Southern Shores Board of Adjustment** as established by **the Town**, hereinafter
23 referred to as the "appeal board," shall hear and decide requests for variances from the
24 requirements of this chapter.

25 (2) Any person aggrieved by the decision of the appeal board may appeal such decision to
26 the court, as provided in Chapter 7A of the North Carolina General Statutes.

27 (3) Variances may be issued for:

28 a. The repair or rehabilitation of historic structures upon the determination that the
29 proposed repair or rehabilitation will not preclude the structure's continued
30 designation as a historic structure and that the variance is the minimum necessary
31 to preserve the historic character and design of the structure.

32 b. Functionally dependent facilities, if determined to meet the definition as stated in
33 *Section 16-2; provided provisions of subsection (e)(9)b, c and e of this Section* have
34 been satisfied, and such facilities are protected by methods that minimize flood
35 damages.

36 c. Any other type of development, provided it meets the requirements stated in this
37 Section.

38 (4) In passing upon variances, the appeal board shall consider all technical evaluations, all
39 relevant factors, all standards specified in other sections of this chapter, and:

40 a. The danger that materials may be swept onto other lands to the injury of others;

41 b. The danger to life and property due to flooding or erosion damage;

42 c. The susceptibility of the proposed facility and its contents to flood damage and the
43 effect of such damage on the individual owner;

44 d. The importance of the services provided by the proposed facility to the community;

45 e. The necessity to the facility of a waterfront location as defined under *Section 16-2* of
46 this Chapter as a functionally dependent facility, where applicable;

- 1 f. The availability of alternative locations, not subject to flooding or erosion damage, for
2 the proposed use;
- 3 g. The compatibility of the proposed use with existing and anticipated development;
- 4 h. The relationship of the proposed use to the comprehensive plan and floodplain
5 management program for that area;
- 6 i. The safety of access to the property in times of flood for ordinary and emergency
7 vehicles;
- 8 j. The expected heights, velocity, duration, rate of rise, and sediment transport of the
9 floodwaters and the effects of wave action, if applicable, expected at the site; and
- 10 k. The costs of providing governmental services during and after flood conditions
11 including maintenance and repair of public utilities and facilities such as sewer, gas,
12 electrical and water systems, and streets and bridges.
- 13 (5) A written report addressing each of the factors shall be submitted with the application for
14 a variance.
- 15 (6) Upon consideration of the factors listed above and the purposes of this Chapter, the
16 appeal board may attach such conditions to the granting of variances as it deems
17 necessary to further the purposes of this Chapter.
- 18 (7) Any applicant to whom a variance is granted shall be given written notice specifying the
19 difference between the **RFPE** and the elevation to which the structure is to be built and
20 that such construction below the **RFPE** increases risks to life and property, and that the
21 issuance of a variance to construct a structure below the **RFPE** will result in increased
22 premium rates for flood insurance up to \$25 per \$100 of insurance coverage. Such
23 notification shall be maintained with a record of all variance actions, including justification
24 for their issuance.
- 25 (8) The Floodplain Administrator shall maintain the records of all appeal actions and report
26 any variances to the FEMA and the state upon request.
- 27 (9) Conditions for variances.
- 28 a. Variances shall not be issued when the variance will make the structure in violation
29 of other federal, state, or local laws, regulations, or ordinances.
- 30 b. Variances shall not be issued within any designated floodway or non-encroachment
31 area if the variance would result in any increase in flood levels during the base flood
32 discharge.
- 33 c. Variances shall only be issued upon a determination that the variance is the
34 minimum necessary, considering the flood hazard, to afford relief.
- 35 d. Variances shall only be issued prior to development permit approval.
- 36 e. Variances shall only be issued upon:
- 37 1. A showing of good and sufficient cause;
- 38 2. A determination that failure to grant the variance would result in exceptional
39 hardship; and
- 40 3. A determination that the granting of a variance will not result in increased flood
41 heights, additional threats to public safety, or extraordinary public expense,
42 create nuisance, cause fraud on or victimization of the public, or conflict with
43 existing local laws or ordinances.

- 1 (10) A variance may be issued for solid waste disposal facilities, hazardous waste
2 management facilities, salvage yards, and chemical storage facilities that are located in
3 special flood hazard areas provided that all of the following conditions are met:
- 4 a. The use serves a critical need in the community.
 - 5 b. No feasible location exists for the use outside the special flood hazard area.
 - 6 c. The reference level of any structure is elevated or floodproofed to at least the
7 regulatory flood protection elevation.
 - 8 d. The use complies with all other applicable federal, state and local laws.
 - 9 e. The Town of Southern Shores has notified the Secretary of the North Carolina
10 Department of Public Safety of its intention to grant a variance at least 30 calendar
11 days prior to granting the variance.

12 Sec. 16-5. - Provisions for flood hazard reduction.

13 (a) *General standards.* The following provisions are required:

- 14 (1) All new construction and substantial improvements shall be designed (or modified) and
15 adequately anchored to prevent flotation, collapse, and lateral movement of the structure.
- 16 (2) All new construction and substantial improvements shall be constructed with materials
17 and utility equipment resistant to flood damage in accordance with the FEMA Technical
18 Bulletin 2, *Flood Damage-Resistant Materials Requirements*.
- 19 (3) All new construction and substantial improvements shall be constructed by methods and
20 practices that minimize flood damages.
- 21 **(4) All new electrical, heating, ventilation, plumbing, air conditioning equipment, and**
22 **other service equipment shall be located at or above the RFPE or designed and**
23 **installed to prevent water from entering or accumulating within the components**
24 **during the occurrence of the base flood. These include, but are not limited to,**
25 **HVAC equipment, water softener units, bath/kitchen fixtures, ductwork,**
26 **electric/gas meter panels/boxes, utility/cable boxes, water heaters, and electric**
27 **outlets/switches.**
 - 28 **(a) Replacements that are part of a substantial improvement, electrical, heating,**
29 **ventilation, plumbing, air conditioning equipment, and other service equipment**
30 **shall also meet the above provisions.**
 - 31 **(b) Replacements that are for maintenance and not part of a substantial**
32 **improvement, may be installed at the original location provided the addition**
33 **and/or improvements only comply with the standards for new construction**
34 **consistent with the code and requirements for the original structure.**
- 35 (5) All new and replacement water supply systems shall be designed to minimize or eliminate
36 infiltration of floodwaters into the system.
- 37 (6) New and replacement sanitary sewage systems shall be designed to minimize or
38 eliminate infiltration of floodwaters into the systems and discharges from the systems into
39 flood waters.
- 40 (7) On-site waste disposal systems shall be located and constructed to avoid impairment to
41 them or contamination from them during flooding.
- 42 (8) Nothing in this section shall prevent the repair, reconstruction, or replacement of a
43 building or structure existing on the effective date of the ordinance from which this s
44 chapter is derived and located totally or partially within the floodway, non-encroachment

- 1 area, or stream setback, provided there is no additional encroachment below the
2 regulatory flood protection elevation in the floodway, non-encroachment area, or stream
3 setback, and provided that such repair, reconstruction, or replacement meets all of the
4 other requirements of this section.
- 5 (9) New solid waste disposal facilities and sites, hazardous waste management facilities,
6 salvage yards, and chemical storage facilities shall not be permitted, except by variance
7 as specified in *Section 16-4(e)(10)*. A structure or tank for chemical or fuel storage
8 incidental to an allowed use or to the operation of a water treatment plant or wastewater
9 treatment facility may be located in a special flood hazard area only if the structure or
10 tank is either elevated or floodproofed to at least the regulatory flood protection elevation
11 and certified according to *Section 16-4(b)(3)*.
- 12 (10) All subdivision proposals and other development proposals shall be consistent with the
13 need to minimize flood damage.
- 14 (11) All subdivision proposals and other development proposals shall have public utilities and
15 facilities such as sewer, gas, electrical, and water systems located and constructed to
16 minimize flood damage.
- 17 (12) All subdivision proposals and other development proposals shall have adequate drainage
18 provided to reduce exposure to flood hazards.
- 19 (13) All subdivision proposals and other development proposals shall have received all
20 necessary permits from those governmental agencies for which approval is required by
21 federal or state law, including section 404 of the Federal Water Pollution Control Act
22 Amendments of 1972, 33 USC 1334.
- 23 (14) When a structure is partially located in a Special Flood Hazard Area, the entire structure
24 shall meet the requirements for new construction and substantial improvements.
- 25 (15) When a structure is located in multiple flood hazard zones or in a flood hazard risk zone
26 with multiple base flood elevations, the provisions for the more restrictive flood hazard
27 risk zone and the highest **RFPE** shall apply.
- 28 (b) *Specific standards.* The following provisions, in addition to the provisions of Article 5, Section
29 A, are required.
- 30 (1) *Residential construction.* New construction and substantial improvement of any
31 residential structure (including manufactured homes) shall have the reference level,
32 including basement, elevated no lower than the regulatory flood protection elevation, as
33 defined in *Section 16-2*.
- 34 (2) *Nonresidential construction.* New construction and substantial improvement of any
35 commercial, industrial, or other nonresidential structure shall have the reference level,
36 including basement, elevated no lower than the regulatory flood protection elevation, as
37 defined in *Section 16-2*. Structures located in A, AE, AH, AO, **Shaded X and X zone** may
38 be floodproofed to the regulatory flood protection elevation in lieu of elevation provided
39 that all areas of the structure, together with attendant utility and sanitary facilities, below
40 the regulatory flood protection elevation are watertight with walls substantially
41 impermeable to the passage of water, using structural components having the capability
42 of resisting hydrostatic and hydrodynamic loads and the effect of buoyancy. For AO
43 zones, the floodproofing elevation shall be in accordance with *Section 16-5(g)*. A
44 registered professional engineer or architect shall certify that the standards of this
45 subsection are satisfied. Such certification shall be provided to the floodplain
46 administrator as set forth in *Section 16-4(b)(3)*, along with the operational and
47 maintenance plans.
- 48 (3) *Manufactured homes.*

- 1 a. New or replacement manufactured homes shall be elevated so that the reference
2 level of the manufactured home is no lower than the regulatory flood protection
3 elevation, as defined in *Section 16-2*.
- 4 b. Manufactured homes shall be securely anchored to an adequately anchored
5 foundation to resist flotation, collapse, and lateral movement, either by engineer
6 certification, or in accordance with the most current edition of the state regulations
7 for manufactured homes, adopted by the commissioner of insurance pursuant to
8 G.S. 143-143.15 or a certified engineered foundation. Additionally, when the
9 elevation would be met by an elevation of the chassis 36 inches or less above the
10 grade at the site, the chassis shall be supported by reinforced piers or an engineered
11 foundation. When the elevation of the chassis is above 36 inches in height, an
12 engineering certification is required.
- 13 c. All enclosures or skirting below the lowest floor shall meet the requirements of
14 subsections (b)(4) of this section.
- 15 d. An evacuation plan must be developed for evacuation of all residents of all new,
16 substantially improved or substantially damaged manufactured home parks or
17 subdivisions located within floodprone areas. This plan shall be filed with and
18 approved by the floodplain administrator and the local emergency management
19 coordinator.
- 20 (4) *Elevated buildings. Fully enclosure/enclosed areas as defined in Section 16-2 of*
21 *new construction and substantially improved structures, which are below the*
22 *lowest floor in AE, AO, AH, Shaded X or X zones or below the lowest horizontal*
23 *structural member in VE zones:*
- 24 a. Shall not be designed or used for human habitation, but shall only be used for parking
25 of vehicles, building access, or limited storage of maintenance equipment used in
26 connection with the premises. Access to the enclosed area shall be the minimum
27 necessary to allow for parking of vehicles (garage door) or limited storage of
28 maintenance equipment (standard exterior door), or entry to the living area (stairway
29 or elevator). The interior portion of such enclosed area shall not be finished or
30 partitioned into separate rooms, except to enclose storage areas;
- 31 b. **Shall not be temperature-controlled or conditioned. Non-temperature**
32 **controlled dehumidifiers may be used in enclosed areas and shall not result**
33 **in the enclosed area being determined to be conditioned space.**
- 34 c. Shall be constructed entirely of flood resistant materials; and
- 35 d. Shall include, in zones A, AE, AH, AO, **Shaded X and X zones** flood openings to
36 automatically equalize hydrostatic flood forces on walls by allowing for the entry and
37 exit of floodwaters. To meet this requirement, the openings must either be certified
38 by a professional engineer or architect or meet or exceed the following minimum
39 design criteria:
40
41
- 42 1. A minimum of two flood openings on different sides of each enclosed area
43 subject to flooding;
- 44 2. The total net area of all flood openings must be at least one square inch for
45 each square foot of enclosed area subject to flooding; **or a minimum of one**
46 **engineered inch for each square foot of enclosed area for an engineered**
47 **opening.**
- 48 3. If a building has more than one enclosed area, each enclosed area must have
49 flood openings to allow floodwaters to automatically enter and exit;

- 1 4. The bottom of all required flood openings shall be no higher than one foot above
2 the **interior or exterior** adjacent grade;
 - 3 5. Flood openings may be equipped with screens, louvers, or other coverings or
4 devices, provided they permit the automatic flow of floodwaters in both
5 directions; and
 - 6 6. Enclosures made of flexible skirting are not considered enclosures for
7 regulatory purposes and, therefore, do not require flood openings. Masonry or
8 wood underpinning, regardless of structural status, is considered an enclosure
9 and requires flood openings as outlined in this subsection.
- 10 e. Shall allow, in Coastal High Hazard Areas (Zone VE), breakaway walls, open wood
11 latticework or insect screening, provided it is not part of the structural support of the
12 building and is designed so as to breakaway, under abnormally high tides or wave
13 action, without causing damage to the structural integrity of the building, provided
14 the following design specifications are met:
- 15 1. Material shall consist of open wood latticework or insect screening; or
 - 16 2. Breakaway walls shall meet the following design specifications:
 - 17 (i) Design safe loading resistance of each wall shall be not less than ten nor
18 more than 20 pounds per square foot; or
 - 19 (ii) Breakaway walls that exceed a design safe loading resistance of 20
20 pounds per square foot (either by design or when so required by state or
21 local codes) shall be certified by a registered professional engineer or
22 architect that the breakaway wall will collapse from a water load less than
23 that which would occur during the base flood event, and the elevated
24 portion of the building and supporting foundation system shall not be
25 subject to collapse, displacement, or other structural damage due to the
26 effects of wind and water loads acting simultaneously on all building
27 components (structural and nonstructural). The water loading values used
28 shall be those associated with the base flood. The wind loading values
29 used shall be those required by the state building code.

30 (5) *Additions/improvements.*

31 **a. In AE, AO and VE Zones**

- 32 i. Additions and/or improvements to pre-FIRM structures when the addition and/or
33 improvements in combination with any interior modifications to the existing structure
34 are:
 - 35 1. Not a substantial improvement, the addition and/or improvements must be
36 designed to minimize flood damages and must not be any more nonconforming
37 than the existing structure.
 - 38 2. A substantial improvement with **modification rehabilitations/improvements**
39 **to the existing structure or the common wall is structurally modified**
40 **more than installing a doorway, both the existing structure and the**
41 **addition must comply with the standards for new construction.**
- 42 ii. Additions to pre-FIRM or post-FIRM structures that are a substantial improvement
43 with no modifications/rehabilitations/improvements to the existing structure other
44 than a standard door in the common wall, shall require only the addition to comply
45 with the standards for new construction.

1 iii. Additions and/or improvements to post-FIRM structures when the addition and/or
2 improvements in combination with any interior modifications to the existing structure
3 are:

4 1. Not a substantial improvement, the addition and/or improvements only must
5 comply with the standards for new construction consistent with the code and
6 requirements for the original structure.

7 2. A substantial improvement, both the existing structure and the addition and/or
8 improvements must comply with the standards for new construction.

9 **iv. Any combination of repair, reconstruction, rehabilitation, addition or**
10 **improvement of a building or structure taking place during 1-year period, the**
11 **cumulative cost of which equals or exceeds 50 percent of the market value of**
12 **the structure before the improvement or repair is started must comply with the**
13 **standards for new construction. For each building or structure, the 1-year**
14 **period begins on the date the Certificate of Occupancy is issued for the first**
15 **improvement or repair of that building or structure subsequent to the effective**
16 **date of this ordinance. The term "substantial damage" also means flood-**
17 **related damage sustained by a structure on two separate occasions during a**
18 **ten-year period for which the cost of repairs at the time of each such flood**
19 **event, on the average, equals or exceeds 25 percent of the market value of the**
20 **structure before the damage occurred. If the structure has sustained**
21 **substantial damage, any repairs are considered substantial improvement**
22 **regardless of the actual repair work performed. The requirement does not,**
23 **however, include either:**

24
25 **(1) Any project for improvement of a building required to correct existing**
26 **health, sanitary or safety code violations identified by the building official**
27 **and that are the minimum necessary to assume safe living conditions.**

28
29 **(2) Any alteration of a historic structure provided that the alteration will not**
30 **preclude the structure's continued designation as a historic structure.**

31
32 **(v) Areas in existing structures shall not be converted for use as conditioned,**
33 **temperature controlled space unless the reference level is located to or above**
34 **the RFPE.**

35
36 **b. In Shaded X and X Zones**

37
38 i. **The substantial improvement/substantial damage definitions as established**
39 **in Article 2, Definitions, do not apply to Shaded X and X Zones.**

40
41 ii. **Laterals additions (increase in the footprint of the conditioned,**
42 **temperature-controlled space) to existing structures shall have the**
43 **reference level elevated to or above the RFPE that was applicable at the**
44 **time of original construction of the structure.**

45
46 iii. **Remodeling or renovations of existing structures with the reference level**
47 **located below the current applicable RFPE that do not increase the**

1 footprint of the structure may be authorized at the existing reference level
2 or higher.

3
4 iv. Reconstruction of damaged portions of a structure may be authorized at
5 the existing reference level or higher. However, if a structure is entirely
6 demolished for whatever reason, the replacement structure shall be
7 constructed to or above the RFPE.

8
9 v. Structures that are relocated on the same site or to another site shall be
10 elevated to or above the applicable RFPE of the lot or to or above the RFPE
11 of the new site.

12
13 vi. Areas in existing structures shall not be converted for use as conditioned,
14 temperature controlled space unless the reference level is located to or
15 above the RFPE.

16
17 **(6) Recreational Vehicles. Recreational vehicles shall either:**

18
19 **a. Temporary Placement**

20
21 **(i) Be on site for fewer than 180 consecutive days; or**

22
23 **(ii) Be fully licensed and ready for highway use. (A recreational vehicle is**
24 **ready for highway use if it is on its wheels or jacking system, is attached**
25 **to the site only by quick disconnect type utilities, and has no**
26 **permanently attached additions.)**

27
28 **b. Permanent Placement. Recreational vehicles located in travel trailer parks**
29 **authorized by the Town that do not meet the limitations of Temporary Placement**
30 **shall meet all the requirements for new construction.**

31
32 **(7) Temporary nonresidential structures.** Prior to the issuance of a floodplain development
33 permit for a temporary structure, the applicant must submit to the floodplain administrator
34 a plan for the removal of such structure in the event of a hurricane, flash flood or other
35 type of flood warning notification. The following information shall be submitted in writing
36 to the floodplain administrator for review and written approval:

37 a. A specified time period for which the temporary use will be permitted. Time specified
38 should not exceed three months, renewable up to one year;

39 b. The name, address, and phone number of the individual responsible for the removal
40 of the temporary structure;

41 c. The time frame prior to the event at which a structure will be removed (i.e., minimum
42 of 72 hours before landfall of a hurricane or immediately upon flood warning
43 notification);

44 d. A copy of the contract or other suitable instrument with the entity responsible for
45 physical removal of the structure; and

1 e. Designation, accompanied by documentation, of a location outside the special flood
2 hazard area, to which the temporary structure will be moved.

3 (8) *Accessory structures.* When accessory structures (sheds, detached garages, etc.) are
4 to be placed within a special flood hazard area, the following criteria shall be met:

5 a. Accessory structures shall not be used for human habitation (including working,
6 sleeping, living, cooking or restroom areas) unless permitted by the town's zoning
7 ordinance and all such permissible habitable space is located above the regulatory
8 flood protection elevation;

9 b. Accessory structures shall not be temperature-controlled unless permitted by the
10 town's zoning ordinance and all such permissible temperature-controlled space is
11 located above the regulatory flood protection elevation;

12 c. Accessory structures shall be designed to have low flood damage potential;

13 d. Accessory structures shall be constructed and placed on the building site so as to
14 offer the minimum resistance to the flow of floodwaters;

15 e. Accessory structures shall be firmly anchored in accordance with *Section 16-5(a)(1)*;

16 f. Accessory structures, regardless of the size or cost, shall not be placed below
17 elevated buildings in V and VE Zones;

18 g. All service facilities such as electrical shall be installed in accordance with *Section*
19 *16-5 (a)(4)*; and
20

21 h. Flood openings to facilitate automatic equalization of hydrostatic flood forces shall
22 be provided below regulatory flood protection elevation in conformance with *Section*
23 *16-5 (b)(4)d* of this section. An accessory structure with a footprint less than 150
24 square feet that satisfies the criteria outlined in this subsection does not require an
25 elevation or floodproofing certificate unless it has habitable space or temperature
26 controlled space. Elevation or floodproofing certifications are required for all other
27 accessory structures in accordance with *Section 16-4(b)(3)*.

28 i. Residential accessory structures existing as of January 1, 2017 which were otherwise
29 lawful and duly permitted at the time of their construction or modification and which
30 are nonconforming due solely to the inclusion of working, sleeping, living, cooking
31 or restroom space within the accessory structure shall be considered legally
32 nonconforming under this chapter so long as all such working, sleeping, living,
33 cooking or restroom space is located above regulatory flood protection elevation.
34 Such accessory structures may be modified in conformance with this chapter and
35 the nonconforming working, sleeping, living, cooking or restroom space within them
36 may continue so long as the nonconformity is not expanded.

37 j. **Exemptions:**

38 i. **Accessory use structures 150 square feet or less are exempt from the**
39 **certification requirements of Section 16-4(b) (3) (a).**

40
41 **k. Other structures located on the same parcel in addition to a principal use**
42 **structure which feature conditioned, temperature controlled areas elevated above**
43 **the regulatory flood protection elevation shall be constructed consistent with**
44 **Section 16-5 (a) (b). The certification requirements of Section 16-4 (b) (3) (a) shall**
45 **apply.**

46
47 (9) **Tanks. Gas and liquid storage tanks shall meet the following criteria:**

48
49 a. **Underground tanks. Underground tanks in flood hazard areas shall be anchored**

1 to prevent flotation, collapse or lateral movement resulting from hydrodynamic
2 and hydrostatic loads during conditions of the design flood, including the
3 effects of buoyancy assuming the tank is empty; or
4

- 5 b. Above-ground tanks, elevated. Above-ground tanks in flood hazard areas may
6 be elevated to or above the Regulatory Flood Protection Elevation on a
7 supporting structure that is designed to prevent flotation, collapse or lateral
8 movement during conditions of the design flood. Tank-supporting structures
9 shall meet the foundation requirements of the applicable flood hazard area; or
10
- 11 c. Above-ground tanks, not elevated. Above-ground tanks that do not meet the
12 elevation requirements of Section 16-5 (b)(2) of this ordinance shall not be
13 permitted in V or VE Zones. Tanks may be permitted in other flood hazard areas
14 provided the tanks are designed, constructed, installed, and anchored to resist
15 all flood-related and other loads, including the effects of buoyancy and lateral
16 movement, during conditions of the design flood and without release of contents
17 in the floodwaters or infiltration by floodwaters into the tanks. Tanks shall be
18 designed, constructed, installed, and anchored to resist the potential buoyant and
19 other flood forces acting on an empty tank during design flood conditions.
20
- 21 d. Tank inlets and vents. Tank inlets, fill openings, outlets and vents shall be locate
22 at or above the regulatory flood protection elevation or fitted with covers designed
23 to prevent lateral movement, the inflow of floodwater or outflow of the contents
24 of the tanks during conditions of the design flood.
25

26 *(c) Standards for floodplains without established base flood elevations. Within the*
27 *Special Flood Hazard Areas designated as Approximate Zone A and established in Section*
28 *16-3 (b), where no BFE data has been provided by FEMA, the following provisions, in*
29 *addition to the provisions of Section 16-5(a), shall apply:*
30

31 (1) No encroachments, including fill, new construction, substantial improvements
32 or new development shall be permitted within a distance of twenty (20) feet each
33 side from top of bank or five times the width of the stream, whichever is greater,
34 unless certification with supporting technical data by a registered professional
35 engineer is provided demonstrating that such encroachments shall not result in
36 any increase in flood levels during the occurrence of the base flood discharge.
37

38 (2) The BFE used in determining the Regulatory Flood Protection Elevation shall
39 be determined based on the following criteria:
40

41 a. When BFE data is available from other sources, all new construction and
42 substantial improvements within such areas shall also comply with all applicable
43 provisions of this ordinance and shall be elevated or floodproofed in accordance
44 with standards in Sections 16-5 (a) and (b).
45

46 b. When floodway or non-encroachment data is available from a Federal, State, or
47 other source, all new construction and substantial improvements within floodway
48 and non-encroachment areas shall also comply with the requirements of Sections
49 16-5 (b) and (f).
50

51 c. All subdivision, manufactured home park and other development proposals
52 shall provide BFE data if development is greater than five (5) acres or has more
53 than fifty (50) lots/manufactured home sites. Such BFE data shall be adopted by
54 reference in accordance with Section 16-3(b), and utilized in implementing this
55 ordinance.

1
2 d. When BFE data is not available from a Federal, State, or other source as
3 outlined above, the reference level shall be elevated or floodproofed
4 (nonresidential) to or above the Regulatory Flood Protection Elevation, as defined
5 in Section 16-2. All other applicable provisions of, Section 16-5 (b) shall also apply.
6

7 *(d) Standards for riverine floodplains with base flood elevations but without established*
8 *floodways or non-encroachment areas.* Along rivers and streams where BFE data is
9 provided by FEMA or is available from another source but neither floodway nor non-
10 encroachment areas are identified for a Special Flood Hazard Area on the FIRM or in the
11 FIS report, the following requirements shall apply to all development within such areas:
12

- 13 (1) Standards of *Section 16-5(a) and (b)* and
- 14
- 15 (2) Until a regulatory floodway or non-encroachment area is designated, no
16 encroachments, including fill, new construction, substantial improvements,
17 or other development, shall be permitted unless certification with
18 supporting technical data by a registered professional engineer is provided
19 demonstrating that the cumulative effect of the proposed development,
20 when combined with all other existing and anticipated development, will
21 not increase the water surface elevation of the base flood more than one (1)
22 foot at any point within the community.
23

24 *(e) Floodways and non-encroachment areas.* Areas designated as floodways or non-
25 encroachment areas are located within the Special Flood Hazard Areas established in
26 *Section 16-3 (b)*. The floodways and non-encroachment areas are extremely hazardous
27 areas due to the velocity of floodwaters that have erosion potential and carry debris and
28 potential projectiles. The following provisions, in addition to standards outlined in *Section*
29 *16-5 (a) and (b)*, shall apply to all development within such areas:
30

31 1. No encroachments, including fill, new construction, substantial improvements
32 and other developments shall be permitted unless:
33

34 a. It is demonstrated that the proposed encroachment would not result in
35 any increase in the flood levels during the occurrence of the base flood
36 discharge, based on hydrologic and hydraulic analyses performed in
37 accordance with standard engineering practice and presented to the
38 Floodplain Administrator prior to issuance of floodplain development
39 permit; or
40

41 b. A Conditional Letter of Map Revision (CLOMR) has been approved by
42 FEMA. A Letter of Map Revision (LOMR) must also be obtained within six
43 months of completion of the proposed encroachment.
44

45 2. If *Section 16-5 (f)(1)* is satisfied, all development shall comply with all
46 applicable flood hazard reduction provisions of this ordinance.
47

48 3. Manufactured homes may be permitted provided the following provisions
49 are met:
50

51 a. The anchoring and the elevation standards of *Section 16-5 (b) (3)*; and
52

53 b. The encroachment standards of *Section 16-5 (f) (1)*.
54

1 (f) *Coastal high hazard areas (zones VE)*. Coastal High Hazard Areas are Special Flood Hazard
2 Areas established in *Section 16-3 (b)*, and designated as Zones VE. These areas have special
3 flood hazards associated with high velocity waters from storm surges or seismic activity and,
4 therefore, all new construction and substantial improvements shall meet the following provisions
5 in addition to the provisions of, *Section 16-5 (a) and (b)*:
6

- 7 (1) All new construction and substantial improvements shall:
8 a. Be located landward of the reach of mean high tide;
9 b. Comply with all applicable CAMA setback requirements.
- 10 (2) All new construction and substantial improvements shall be elevated so that the bottom
11 of the lowest horizontal structural member of the lowest floor (excluding pilings or
12 columns) is no lower than the regulatory flood protection elevation. Floodproofing shall
13 not be utilized on any structures in coastal high hazard areas to satisfy the regulatory
14 flood protection elevation requirements.
- 15 (3) All new construction and substantial improvements shall have the space below the
16 lowest floor free of obstruction so as not to impede the flow of floodwaters, with the
17 following exceptions:
18 a. Open wood latticework or insect screening may be permitted below the regulatory
19 flood protection elevation for aesthetic purposes only and must be designed to wash
20 away in the event of abnormal wave action and in accordance with *Section 16-5*
21 *(b)(4)d.1* of this section. Design plans shall be submitted in accordance with *Section*
22 *16-4 (b)(1)d.3.(ii)*; or
23 b. Breakaway walls may be permitted provided they meet the criteria set forth in *Section*
24 *16-5 (b)(4)e.2* of this section. Design plans shall be submitted in accordance with
25 *Section 16-4(b)(1)d.3.(i)*.
- 26 (4) All new construction and substantial improvements shall be securely anchored to pile or
27 column foundations. All pilings and columns and the structures attached thereto shall be
28 anchored to resist flotation, collapse, and lateral movement due to the effect of wind and
29 water loads acting simultaneously on all building components.
30 a. Water loading values used shall be those associated with the base flood.
31 b. Wind loading values used shall be those required by the current edition of the state
32 building code.

33 **(5) For concrete pads, including patios, decks, parking pads, walkways,**
34 **driveways, pool decks, etc. the following is required:**
35

36 **a. Shall be structurally independent of the primary structural foundation**
37 **system of the structure and shall not adversely affect structures through**
38 **redirection of floodwaters or debris; and**
39

40 **b. Shall be constructed to breakaway cleanly during design flood conditions,**
41 **shall be frangible, and shall not produce debris capable of causing damage to**
42 **any structure (Note: The installation of concrete in small segments**
43 **(approximately 4 feet x 4 feet) that will easily break up during the base flood**
44 **event, or score concrete in 4 feet x 4 feet maximum segments is acceptable to**
45 **meet this standard; and**
46

1 c. Reinforcing, including welded wire fabric, shall not be used in order to
2 minimize the potential for concreted pads being a source of debris; and

3
4 d. Pad thickness

5 (1) Shall not exceed 4 inches; or

6
7 (2) Be certified by a design professional that the design and method of
8 construction to be used shall be compliant with the applicable criteria of
9 this section.

10
11 e. The provisions above shall not apply to non-residential or multi-family
12 construction that is designed by a professional engineer and constructed with
13 self-supporting structural slabs capable of remaining intact and functional
14 under base flood conditions, including expected erosion.

15
16
17 (6) For swimming pools and spas, the following is required:

18
19 a. Be designed to withstand all flood-related loads and load combinations.

20
21 (1) Be elevated so that the lowest horizontal structural member is elevated
22 above the RFPE; or

23
24 (2) Be designed and constructed to break away during design flood
25 conditions without producing debris capable of causing damage to any
26 structure; or

27
28 (3) Be sited to remain in the ground during design flood conditions without
29 obstructing flow that results in damage to any structure.

30
31 b. Registered design professionals must certify to local officials that a pool or spa
32 beneath or near a VE Zone building will not be subject to flotation or
33 displacement that will damage building foundations or elevated portions of the
34 building or any nearby buildings during a coastal flood.

35
36 (7) All elevators, vertical platform lifts, chair lifts, etc., the following is required:

37
38 a. Elevator enclosures must be designed to resist hydrodynamic and
39 hydrostatic forces as well as erosion, scour, and waves.

40
41 b. Utility equipment in Coastal High Hazard Areas (VE Zones) must not be
mounted on, pass through, or be located along breakaway walls.

42
43 c. The cab, machine/equipment room, hydraulic pump, hydraulic reservoir,
44 counter weight and roller guides, hoist cable, limit switches, electric hoist
45 motor, electrical junction box, circuit panel, and electrical control panel shall:

46 (1) Be elevated to or above the regulatory flood protection elevation; or

47
48 (2) Constructed using flood damage-resistant components/materials.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51

- (8) A registered professional engineer or architect shall certify that the design, specifications and plans for construction are in compliance with the provisions of *Section 16-4(b) and Section 16-5 (f)(3) and (4)*, on the current version of the North Carolina V-Zone Certification form or equivalent local version. In addition, prior to the Certificate of Compliance/Occupancy issuance, a registered professional engineer or architect shall certify the finished construction is compliant with the design, specifications and plans for VE Zone construction.
- (9) Fill/Grading – **Fill material shall not be used for structural support of a building.** Minor grading and the placement of minor quantities of nonstructural fill may be permitted for landscaping and for drainage proposed under and around buildings, and for support of parking slabs, pool decks, patios and walkways. **Fill material shall not prevent free passage of floodwaters and waves beneath elevated buildings. Fill material must not divert floodwaters or deflect waves such that increased damage is sustained by adjacent or nearby buildings. FEMA Technical Bulletins may be consulted for appropriate evaluation criteria on the placement of nonstructural fill in VE zones.**
- (10) There shall be no alteration of sand dunes or mangrove stands which would increase potential flood damage.
- (11) No manufactured homes shall be permitted except in an existing manufactured home park or subdivision. A replacement manufactured home may be placed on a lot in an existing manufactured home park or subdivision provided the anchoring and elevation standards of this section have been satisfied.
- (12) Recreational vehicles may be permitted in Coastal High Hazard Areas provided that they meet the recreational vehicle criteria of *Section 16-5 (b)(6)a*.
- (13) A deck that is structurally attached to a building or structure shall have the bottom of the lowest horizontal structural member at or above the Regulatory Flood Protection Elevation and any supporting members that extend below the Regulatory Flood Protection Elevation shall comply with the foundation requirements that apply to the building or structure, which shall be designed to accommodate any increased loads resulting from the attached deck. The increased loads must be considered in the design of the primary structure and included in the V-Zone Certification required under *Section 16-4 B, (3)(f)*.
- (14) A deck or patio that is located below the Regulatory Flood Protection Elevation shall be structurally independent from buildings or structures and their foundation systems, and shall be designed and constructed either to remain intact and in place during design flood conditions or to break apart into small pieces to minimize debris during flooding that is capable of causing structural damage to the building or structure or to adjacent buildings and structures.
- (15) In coastal high hazard areas, development activities other than buildings and structures shall be permitted only if also authorized by the appropriate state or local authority; if located outside the footprint of, and not structurally attached to, buildings and structures; and if analyses prepared by qualified registered design professionals demonstrate no harmful diversion of floodwaters or wave run-up and wave reflection that would increase damage to adjacent buildings and structures. Such other development activities include but are not limited to:
 - a. Bulkheads, seawalls, retaining walls, revetments, and similar erosion control structures;

1
2 b. Solid fences and privacy walls, and fences prone to trapping debris, unless
3 designed and constructed to fail under flood conditions less than the design
4 flood or otherwise function to avoid obstruction of floodwaters.
5

6
7 *(g) Standards for areas of shallow flooding (Zone AO)* Located within the Special Flood
8 Hazard Areas established in *Section 16-3 (b)*, are areas designated as shallow flooding
9 areas. These areas have special flood hazards associated with base flood depths of one
10 (1) to three (3) feet where a clearly defined channel does not exist and where the path of
11 flooding is unpredictable and indeterminate. In addition to *Sections 16-5 (a) and (b)*, all
12 new construction and substantial improvements shall meet the following requirements:
13

14 1. The reference level shall be elevated at least as high as the depth number
15 specified on the Flood Insurance Rate Map (FIRM), in feet, ~~plus a freeboard of 3 feet,~~
16 ~~above the highest adjacent grade; to or above~~ ~~or at 8 feet NAVD 1988. whichever is~~
17 ~~greater above the highest adjacent grade if no depth number is specified.~~
18

19 2. Non-residential structures may, in lieu of elevation, be floodproofed to the same
20 level as required in *Section 16-5(h)(1)* so that the structure, together with attendant
21 utility and sanitary facilities, below that level shall be watertight with walls
22 substantially impermeable to the passage of water and with structural components
23 having the capability of resisting hydrostatic and hydrodynamic loads and effects of
24 buoyancy. Certification is required in accordance with *Section 16-4 (b)3* and
25 *Section 16-5 (b)2*.
26

27 3. Adequate drainage paths shall be provided around structures on slopes, to
28 guide floodwaters around and away from proposed structures.
29

30 *(h). Standards for areas of shallow flooding (Zone AH)* Located within the Special Flood
31 Hazard Areas established in *Section 16-3 (b)*, are areas designated as shallow flooding
32 areas. These areas are subject to inundation by 1-percent-annual-chance shallow flooding
33 (usually areas of ponding) where average depths are one (1) to three (3) feet. Base Flood
34 Elevations are derived from detailed hydraulic analyses are shown in this zone. In addition
35 to *Section 16-5 (a) and (b)*, all new construction and substantial improvements shall meet
36 the following requirements:
37

38 1. Adequate drainage paths shall be provided around structures on slopes, to guide
39 floodwaters around and away from proposed structures.
40

41
42 **Section 16-6. Legal status provisions.**
43

44 **(a) Effect on rights and liabilities under the existing flood damage prevention ordinance**
45

46 This ordinance in part comes forward by re-enactment of some of the provisions of the
47 Flood Damage Prevention Ordinance enacted November 27, 1979 as amended, and it is not
48 the intention to repeal but rather to re-enact and continue to enforce without interruption
49 of such existing provisions, so that all rights and liabilities that have accrued thereunder
50 are reserved and may be enforced. The enactment of this ordinance shall not affect any
51 action, suit or proceeding instituted or pending. All provisions of the Flood Damage
52 Prevention Ordinance of the Town of Southern Shores enacted on November 27, 1979, as
53 amended, which are not reenacted herein are repealed.
54

1 The date of the initial Flood Damage Prevention Ordinance for Dare County is October 6,
2 1978.

3
4 **(b) Effect upon outstanding floodplain development permits**

5
6 Nothing herein contained shall require any change in the plans, construction, size, or
7 designated use of any development or any part thereof for which a floodplain development
8 permit has been granted by the Floodplain Administrator or his or her authorized agents
9 before the time of passage of this ordinance; provided, however, that when construction is
10 not begun under such outstanding permit within a period of six (6) months subsequent to
11 the date of issuance of the outstanding permit, construction or use shall be in conformity
12 with the provisions of this ordinance.

13
14 **(c) Severability.**

15
16 If any section, clause, sentence, or phrase of the Ordinance is held to be invalid or
17 unconstitutional by any court of competent jurisdiction, then said holding shall in no way
18 effect the validity of the remaining portions of this Ordinance.

19
20
21 **(d) Effective date.**

22
23 This ordinance shall become effective June 19, 2020.

24
25
26 **(e) Adoption certification**

27
28 I hereby certify that this is a true and correct copy of the Flood Damage Prevention
29 Ordinance as adopted by the Town Council of The Town of Southern Shores, North
30 Carolina, on the Day (number or text) day of Month, Year.

31
32 WITNESS my hand and the official seal of insert Name, Title, this the Day (number or text)
33 day of Month, Year.

34
35
36
37 _____
38 Mayor

39 ATTEST:

Date: _____

40
41 _____
42 Town Clerk

Vote: Ayes Naves

43
44
45 APPROVED AS TO FORM:

46
47
48 _____ Town Attorney